

PRO-PARK 8S (PARKING LIFT)

SPECIFICATIONS

Capacity	3629kgs (8,000 lbs.)
Lifting Height	1829mm
Overall Length w/Approach Ramps	5271mm
Overall width (with motor)	2921mm
Runway Width	483mm
Runway Length	4204mm
Drive through width	2045mm
Clearance Between Columns	2388mm
Clearance Between Runways	940mm

FEATURES

- Designed and Tested to rigid industry standards
- Two hydraulic cylinders
- Powder coat finish
- The Lift is Mobile and provided with Casters wheels
- Adjustable height, width and length
- Mounting accessories included
- ALI / ETL Certified Lift
- Single Point Lock release
- FREE Wheel Caster kit and Drip tray included
- Rolling Jack optional



DBS35A (WHEEL ALIGNMENT SCISSORS LIFT)

FEATURES

- Hydraulic system synchronizes the movement of runways
- Integrated limit switch controls high and low lift positions
- Easy-to-use and maintain control panel features push button controls
- Machine available as Flush Type or Surface Mounted

SPECIFICATIONS

Lifting Capacity	3500kgs (7,716 lbs.)
Lifting Height	1525mm / 1825mm*
Lowered Height	FLAT / 300mm*
Overall Length	4470mm / 5680mm*
Overall Width (max)	2283mm
Runway Length	4000mm
Maximum Wheelbase	3488mm / 3578mm*
Runway Width	625mm
Standard Electrical Power	3 Phase, 380V, 50 Hz
Compressed Air Connection	6-8 bar (85-115 psi)

* for surface mounted option

Rolling Jack and LED Runway Lights are optional



AUTHORISED DEALER



Rotary Lift Consolidated (Haimen) Co. Ltd.

1388, Jiangsu Xiushan Road, Haimen

Ph. : 0513 -81,261,269

E-mail : sales@rotarylifftasia.com

Website : www.vsgdover.com

DIRECT LIFT

CHOOSE THE DIRECT ROUTE



CAR



SEDAN



SUV



PICK-UP

LCV

PARKING

Direct-Lift

www.directlift.com

www.directlift.com

PRO-9D PLUS (TWO POST CLEAR FLOOR)

FEATURES

- Padded shut-off bar to prevent damage caused by lifting a vehicle too high
- Reliable, self-setting locking system with easy to reach lock latch handle
- Powder coat finish - more durable than conventional finishes
- Symmetric 2-post lift with Asymmetric arm design provide more pickup points than ever before
- Two heavy-duty hydraulic cylinders designed to minimize down-time by requiring little maintenance
- Spring operated arm restraints, disengage at floor level
- Truck (SUV / MUV) adapters and bracket included

SPECIFICATIONS

Capacity	4082kgs (9,000 lbs.)
Overall Height	3642mm
Shut-Off Height	3499mm
Minimum Ceiling Height	3658mm
Maximum Lifting Height	1930mm
Front Arm Reach	711mm - 1054mm
Rear Arm Reach	800mm - 1137mm
Overall Floor Width	3353mm
Inside Column Width	2769mm
Drive Through	2515mm
Power	3 Phase, 380V, 50Hz 1 Phase, 230V, 50Hz
Motor	2HP



PRO-9F (TWO POST BASE TYPE)

FEATURES

- Commercial grade
- Powder coat finish
- Symmetric arms
- Truck (SUV / MUV) adapters included
- Base plate model

SPECIFICATIONS

Capacity	4082kgs (9,000 lbs.)
Lifting Height	2006mm
Overall Height	2819mm
Lifting Time	45 seconds
Inside Column	2819mm
Overall Floor Width	3518mm
Drive Through	2565mm
Motor	2HP
Power	3 Phase, 380V, 50Hz 1 Phase, 220V, 50Hz



DS7000N/I (SCISSORS LIFT)

SPECIFICATIONS

Lifting Capacity	3175kgs (7000 lbs.)
Lifting Height (without rubber pad)	1820mm / 2010mm*
Minimum Height	189mm
Overall Width	1960mm / 1970mm*
Overall Length	4208mm / 2997mm*
Width of Platforms	530mm
Length of Platforms	1450mm / 1550mm*
Width Between Platforms	987mm / 910mm*
Motor Power	2.2kw
Power	3Phase, 380V, 50Hz

* for Flush Type option



FEATURES

- Controlled by dual hydraulic cylinders
- Adjustable platform extensions to adapt for vehicle length
- Platform is Electro-hydraulic operation
- Air operated safety locks
- Comes with Photo Sensors as safety device
- Includes Rubber Pads
- Available as Surface Mounted (N) or Flush Type (I) options

HF9000 / HF9000A (FOUR POST LIFT)

SPECIFICATIONS

Lifting Capacity	4082kgs (9000 lbs.)
Overall Length (with ramp)	5337mm
Overall Width (with motor)	3276mm
Width of Runways	508mm
Length of Runways	4500mm
Width Between Runways	1000mm
Inside Width of Columns	2716mm
Inside Length of Columns	4190mm
Drive-Thru Clearance	2330mm
Motor	2.2kw
Power	3Phase, 380V, 50Hz



FEATURES

- Electro-hydraulic operation
- HF9000A model includes the AK4T bolt-on alignment kit (radius gauges not included) and Rolling Jack
- Optional: Air pump for Rolling Jack (ProJack-Kit)
- Powder Coat Finish
- Available as HF9000 (Only Four Post) and HF9000A (with wheel alignment) options

PRO-6MR (MID-RISE)

FEATURES

- Powder coat finish
- Two hydraulic cylinders
- Safety locks at any working height with 7 locking positions
- Single point lock release
- 30 second lifting time
- Commercial grade
- Portable, easy to move
- Separate motor stand included

SPECIFICATIONS

Lifting Capacity	2721Kgs (6000lbs.)
Lifting Height	1368mm
Minimum Height	127mm
Overall Length	2098mm
Overall Width	1038mm
Power Options	1 Phase, 230V, 50Hz

